



MC 18 -4WD

BILL TO:

Company Name
Street Address
City, P/Code

DATE:

REF:
FOR:

PROFORMA INVOICE
MC 18-4WD

Basic specifications :

Engine: Kubota V1505 - 26,5Kw - 4 cylinders - 1 498 cm³
Transmission : Hydrostatic

Driver's cab

Standard overhead protector without Windshield, with roof windshield.
Overall height: 2 145 mm
Document case (net)
12V electric plug on instrument panel
Inner rear view mirror
Plastic seat Grammer MSG 20 mechanic

Mast, carriage and forks

FULL VISIBILITY DUPLEX (FVD) 3700 mm
Carriage FEM 2A Class 1260 mm
2 Forks: Forks (length x width x height) 1 150 x 100 x 35 mm

Features

Distributors Control in Cross 2 hydraulic movements

Tyres

Front: All Terrain Profile (Overall width 1430mm) SOLIDEAL 12,5/80-18/12 SL R4
Rear: All Terrain Profile (Overall width 1430mm) SOLIDEAL 27x10-12 SKS (XTRA)
Front enlargers of wings Overall width 1400 mm

Security

Standard Filtration (Without prefilter) rain cap
Exhaust system with exit in the counterweight
Fuel tank locking cap
Battery cut-off

Transmission

Command "passing 4 to 2 drive wheel"
Differential lock on front axle
Hydraulic inching cut-off

Australian Options

Exterior right rear view mirror
Complete road lighting (front / rear)
LED rotating beacon
Reversing light LED
Cyclonic prefilter
Front fender flares extensions overall width 1400 mm
Distributor control in cross 3 elements (2 double action elements + 1 single action)
Audio warning in reverse
Load Back Rest 1260 mm
Shock absorber of load